

WELDED VINYL REPLACEMENT WINDOW TILT SLIDER

Product Series Number:	CVT-260
Applications:	Residential, Light Duty Commercial
Frame Depth:	3-1/4"
Glass Unit Thickness:	7/8"
Dimension Limitation:	Minimum: W=27" H=15" Maximum: W=60" H=50"

Architecture Specifications

General: Manufactured by Crystal Window & Door Systems, Ltd., 31-10 White stone Expwy., Flushing, NY 11354.

Operation: Both sashes shall move left and right. Both sash shall tilt in for ventilation and cleaning exterior glass surface.

Materials: All vinyl extrusions shall be rigid 100% virgin PVC. Frame and sash rails shall have a main wall thickness of 0.075". Frame profile shall have six tubular hollows for strength and thermal efficiency. Sash profiles shall have four tubular hollows.

Frame construction: Frame shall be either fitted with a head expander and sill extension or ultrasonic point welded with nailing fin or J trim. All corners shall be mitered and fusion welded. Frame depth shall be 3.250".

Sash construction: All sash corners shall be mitered and fusion welded. There shall be integral interlock at the meeting rail. Height over 40" shall have metal reinforcements at meeting rails.

Glazing: Both sashes shall utilize 7/8" thick insulating glass consisting of two sheets of 3/32" thick clear annealed glass and a desiccant filled metal spacer system (intercept insulating unit). A butyl sealant shall be extruded around the entire perimeter of the spacer to achieve a seal. Both sashes shall be interior glazed, back bedded with silicone, and utilize dual durometer snap-in glazing beads.

Screen construction: Standard screen shall be a full screen. The screen rails shall be extruded of aluminum with all corners keyed. The screen mesh shall be held-in-place with a flexible spline.

Hardware: Die cast pivot bars shall be inserted into the knob of the shoes, which lock in place once sash is tilted in. Sash lock shall be cam type and finished to match the vinyl extrusion color. Sash lock shall be fastened at the lock rail by two self-tapping color matched screws. Double locks standard on window height over 24". Two vent locks shall be located on right sash for opening the window partially.

Weatherstripping: High-density woven pile shall be used in combination with continuous polyethylene rigid seal to minimize air infiltration.

Finish: Shall be solid vinyl in off white.

Options: Grids – Colonial, Georgian and Diamond aluminum in-glass in white, bronze or two tone (green-white or bronze-white), are available. Glazing – Swiggle glass units, obscure wire, clear wire, frosted, Low-E, Argon filled Low-E, and special tempered glass can be used. Field mulled or factory mulled units are available. Nailing fin can be used for new construction. Two tone colors are available. Rollformed aluminum screens are available.